



## FACED PANEL

### PORO ROVERE LK82

SUPPORT: Chipboard, MDF  
 FORMAT: 5600 x 2070 mm  
 THICKNESS: from 8 to 38 mm  
 TEXTURE ORIENTATION: Vertical  
 BACK TEXTURE: Poro Rovere  
 NOMINAL OVERTHICKNESS: +0.1 mm

## LAMINATE

### PORO ROVERE LK82

TYPE: HPL  
 FORMAT: 3050 x 1300 mm  
 THICKNESS: 0.6 mm, 0.8 mm  
 —  
 TYPE: CPL  
 FORMAT: 1300 mm  
 THICKNESS: from 0.2 to 0.4 mm  
 —  
 TYPE: HyperFlex  
 FORMAT: 1300 mm  
 THICKNESS: 0.1 mm, 0.15 mm, 0.2 mm

## EDGE

### PORO ROVERE LK82

TYPE: ABS  
 HEIGHT: from 15 to 330 mm  
 THICKNESS: from 0.5 to 2.0 mm



## FACED PANEL

### PORO ROVERE LK82

SUPPORT: MDF  
 FORMAT: 5600 x 2150 mm  
 THICKNESS: 4 mm, 6 mm  
 TEXTURE ORIENTATION: Vertical  
 NOMINAL OVERTHICKNESS: +0.05 mm

## LAMINATE

### PORO ROVERE LK82

TYPE: CPL  
 FORMAT: 1300 mm  
 THICKNESS: 0.2 mm  
 —  
 TYPE: HyperFlex  
 FORMAT: 1300 mm  
 THICKNESS: 0.1 mm, 0.15 mm, 0.2 mm

## EDGE

### PORO ROVERE LK82

TYPE: ABS  
 HEIGHT: from 15 to 350 mm  
 THICKNESS: from 0.5 to 2.0 mm  
 —  
 TYPE: BTP  
 HEIGHT: from 15 to 330 mm  
 THICKNESS: 0.3 mm