



Issued according to the Regulation EU CPR 305/2011

- DOP N°: DOP-03
1. Unique identification code of the product: NTX Melamine faced particle board P2
8 – 40 mm thickness
2. Intended use: Wood-based panels for internal use as non-structural components in dry conditions
3. Manufacturer name and address: CLEAF SpA, Via S. Ambrogio 18, 20846 Macherio (MB) - Italy
4. Product Performance Constance Evaluation and Verification System: System 4
5. Notified body: Not applicable
6. Harmonised standard: EN13986:2004+A1:2015
7. Declared performance:

TECHNICAL CHARACTERISTICS EN 13986:2004 +A1:2015	Standard	8-13 mm	14-20 mm	21-25 mm	26-32 mm	33-40 mm
Bending strength Min. [N/mm ²]	EN 310 EN 312	11	11	10,5	9,5	8,5
Internal bond (Tensile strength) Min. [N/mm ²]	EN 319 EN 312	0,40	0,35	0,30	0,25	0,20

MELAMINE FACED PANEL CHARACTERISTICS EN 13986:2004 +A1:2015	Standard	8 mm	9-14 mm	15-17 mm	18-32 mm	33-40 mm
Formaldehyde release	EN ISO 12460-3	≤ 3,5 mg/(m ² h), Class E1 (EN 13986)				
	EN ISO 16516	≤ 0,1 ppm, Class E1 (BANz AT26.11.2018 B2 – E05)				
	ASTM E1333-96	≤ 0,09 ppm (CARB P2 – EPA TSCA Title VI)				
Reaction to fire (intended use)	Standard	Classes of reaction to fire performance (Minimum density 600 kg/m ³)				
Without an air gap behind the panel ^{ab} e	EN 13501-1 EN 13986	E	D-s2,d0	D-s2,d0	D-s2,d0	D-s2,d0
With an air gap ≤ 22 mm behind the panel ^{ce}		E	D-s2,d2	D-s2,d2	D-s2,d2	D-s2,d2
With a closed air gap > 22 mm behind the panel ^{de}		E	E	D-s2,d0	D-s2,d0	D-s2,d0
With an open air gap > 22 mm behind the panel ^{de}		E	E	E	D-s2,d0	D-s2,d0
Any ^e		E				

- a. Mounted without an air gap directly against class A1 or A2-s1, do products with minimum density 10 kg/m³ or at least class D-s2, d2 products with minimum density 400 kg/ m³.
- b. A substrate of cellulose insulation material of at least class E may be included if mounted against the wood-based panel, but not for floorings.

- c. Mounted with an air gap behind. The reverse face of the cavity shall be at least class A2-s1, d0 products with minimum density 10 kg/m³.
- d. Mounted with an air gap behind. The reverse face of the cavity shall be at least class D-s2, d2 products with minimum density 400 kg/m³.
- e. Veneered, phenol- and melamine-faced panels are included for class.

8. The performance of the product identified in points 1. and 2. is in conformity with the declared performance in point 7. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Macherio, 21/11/2023



Lorena De Sario
Quality and After Sales Service Manager